

www.quadrifoglio.com



MELAMINE FACED CHIPBOARD (MFC) TOPS

25 mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC) tops finished with 2 mm matching straight ABS impact resistant edges. Panel density: 670/730 kgs per cubic meter

Finish options:

















FRAME

Powder coated steel tube frame with ø100mm twin wheel lockable castors. 3mm powder coated steel brackets. The two-section MFC top may fold up when not in use hence reducing required room for storage.

Finish options:





LINKING PLATES

Linking plates for back-to-back and end-to-end, we recommend to order linking plates when levelling of tables is required.





TECHNICAL FEATURES









MATERIALS AND RECYCLABILITY

MFC panels used for Serenity range tables are solely manufactured with 100% recycled wood and fully meet requisites of formaldeyde low emissions (CARB Quality Award CATAS Certificate). Rasins used for panels and melamines are free of SVHC substances (to be found in the ECHA list updated as of 12/01/2017).



CERTIFICATES

Constantly receptive to market requirements, Quadrifoglio Sistemi d'Arredo pay special attention on quality and safety contents in order to provide high products and services. The Company has reached certifications UNI EN ISO 9001/2015, UNI EN ISO 14001/2015 and UNI EN ISO 45001/2018 to confirm his policy. Our products are certified and ensured by FSC™ and ECOLOGICAL PANEL.









GREEN ENERGY

The Company had installed the photovoltaic system with 4.500 solar panels in a 7.350 m² surface that covers almost entirely the factory. The photovoltaic is able to produce 1Mw of a quiet green energy, that does not harm the environment and is waste-free. With his high production capacity the photovoltaic allows us to reduce emissions in the atmosphere of all those polluting substances and to those that contribute to the greenhouse effects. Consequently, such measures make us save every year 180 tonne of petrol oil, 440 tonne of CO2, 514kg of sulphur dioxide, 448 kg of nitrogen oxide and 23kg of dust.



TRANSPORT

Detachable systems. Volumes that facilitate the optimization of space. Maximum reduction of energy consumption by transport.