# Quadrifoglio Group

T01

design living

www.quadrifoglio.con



## MFC TOP

30mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC) circular top finished with 2mm matching straight ABS impact resistant edges. Finish options: melamine as well as matt lacquered. Panel density: 670/730 kgs per cubic meter

Finish options:



Tempi di produzione: 5 settimane; oltre alle finiture laccate proposte, tutte le finiture della scala RAL sono disponibili.


## **METAL FRAMES**

Epoxy powder coated steel column base made of a 1.5mm thick ø80mm column and a 6mm Ø500mm base. Translucid seal along the perimeter of the base to prevent marking.

Finish options:



# **LAYOUT**





#### MATERIALS AND RECYCLABILITY

Panels used on T01 range are exclusively 100% made by recycled wood and respect low formaldehyde emission (CATAS certification Quality Award CARB). Resins used on panels and melamine paper are SVHC substances free (reported on ECHA list update to 12/01/2017).



### **CERTIFICATIONS**

Constantly receptive to market requirements, Quadrifoglio Sistemi d'Arredo pay special attention on quality and safety contents in order to provide high products and services. The Company has reached certifications UNI EN ISO 9001/2015, UNI EN ISO 14001/2015 and UNI EN ISO 45001/2018 to confirm his policy. Our products are certified and ensured by FSC™ and ECOLOGICAL PANEL.

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV ISO 9001 • ISO 14001 ISO 45001







## **GREEN ENERGY**

The Company had installed the photovoltaic system with 4.500 solar panels in a 7.350 m² surface that covers almost entirely the factory. The photovoltaic is able to produce 1Mw of a quiet green energy, that does not harm the environment and is waste-free. With his high production capacity the photovoltaic allows us to reduce emissions in the atmosphere of all those polluting substances and to those that contribute to the greenhouse effects. Consequently, such measures make us save every year 180 tonne of petrol oil, 440 tonne of CO2, 514kg of sulphur dioxide, 448 kg of nitrogen oxide and 23kg of dust.



#### **TRANSPORT**

Packaging is reduced in order to decrease volumes. Goods collections are responsibily managed and organised with the aim of optimise transports, reducing atmosphere emissions.