
Quadrifoglio Group





MFC TOP

25mm easy to clean scratch-resistant anti-reflective melamine faced chipboard (MFC) top finished with 2mm matching straight ABS impact resistant edges, radiused corners. Panel density: 670/730 kgs per cubic meter

Finish options:	ВА	GR	ОВ	RK	OL	NO
	White	Grey	Whitened Elm	Oak	Elm	Canaletto walnut

GLASS TOP

10mm back-painted tempered safety floating glass top finished with 1.5mm 45° polished edges, 10mm radiused corners.

Finish options:	S1	l*	
	Light green	White	

* Back painted in a light green finish using scratch-resistant ceramic enamels

METAL FRAME

50×50mm steel square legs complete with ø35mm grey polyethylene 0-15mm adjustable levelling feet. Legs are linked together by a perimeter frame made of 50×20mm steel tubes. Legs and frame supplied epoxy powder coated or chromed.

Finish options:





Ø35mm grey polyethylene 0-15mm adjustable levelling feet.



MATERIALS AND RECYCLABILITY

Panels used on T04 range are exclusively 100% made by recycled wood and respect low formaldehyde emission (CATAS certification Quality Award CARB). Resins used on panels and melamine paper are SVHC substances free (reported on ECHA list update to 12/01/2017).



CERTIFICATIONS

Constantly receptive to market requirements, Quadrifoglio Sistemi d'Arredo pay special attention on quality and safety contents in order to provide high products and services. The Company has reached certifications UNI EN ISO 9001/2015, UNI EN ISO 14001/2015 and UNI EN ISO 45001/2018 to confirm his policy. Our products are certified and ensured by FSC[™] and ECOLOGICAL PANEL.

COMPANY WITH MANAGEMENT SYSTEM CERTIFIED BY DNV ISO 9001 • ISO 14001 ISO 45001





-
_

GREEN ENERGY

The Company had installed the photovoltaic system with 4.500 solar panels in a 7.350 m² surface that covers almost entirely the factory. The photovoltaic is able to produce 1Mw of a quiet green energy, that does not harm the environment and is waste-free. With his high production capacity the photovoltaic allows us to reduce emissions in the atmosphere of all those polluting substances and to those that contribute to the greenhouse effects. Consequently, such measures make us save every year 180 tonne of petrol oil, 440 tonne of CO2, 514kg of sulphur dioxide, 448 kg of nitrogen oxide and 23kg of dust.



TRANSPORT

Packaging is reduced in order to decrease volumes. Goods collections are responsibily managed and organised with the aim of optimise transports, reducing atmosphere emissions.